



## Easy **CLICK**

A particularly interesting novelty of the Corà universe, Easy Click is a wood floor designed for floated laying. As it is based on a modern click together system, no glue is required.

Fitters can therefore lay the floor quickly and easily, with the added bonus that it can be removed and re-installed just as easily and professionally if necessary.

Alternatively, Easy Click can be laid traditionally, in other words by gluing the panels to the subfloor; this guarantees maximum floor stability, even over large surfaces.

Characterised by a resistant finish, Easy Click does not need to be treated with any other type of preserver after being laid.

## Easy CLICK



**PLANK 110**





**PLANK 155**



**PLANK 180**



| WOOD SPECIE   | FINISH     | CHOICE  | WORKING SURFACE | three layers glued-floating<br>14 x 110 x 1100 mm | three layers glued-floating<br>14 x 155 x 1100 mm | three layers glued-floating<br>14 x 180 x 2200 mm |
|---|------------|---------|-----------------|---|---|---|
|  | SOFT TOUCH | NATURAL | light brushing  | <b>80,00</b><br>CBA141101100F3-3                  | <b>88,00</b><br>CBA141551100F3-3                  | <b>105,00</b><br>CBA141802200F3-3                 |
| <b>OAK CBA-F3</b>   |            |         |                 | square edge                                       | square edge                                       | square edge                                       |
|  | NATURAL    | NATURAL | light brushing  | <b>80,00</b><br>CBA141101100F10-3                 | <b>88,00</b><br>CBA141551100F10-3                 | <b>105,00</b><br>CBA141802200F10-3                |
| <b>OAK CBA-F10</b>  |            |         |                 | micro bevel                                       | micro bevel                                       | micro bevel                                       |

### DESCRIPTION

Three-layer prefinished single board oak floor according to the UNI EN 13489 – UNI EN 13756 standards

### FINISH

Material treated with clear matt varnish in layers, which improves resistance to wear.

### WORKING SURFACE

Being lightly brushed, the parquet has a rough surface which exalts the three-dimensional effect.

### LAYING

Laying can be floated or glued. The 5Gc system makes laying faster and reduces the possibility of cracking.






### 5Gc LAYING SYSTEM

The 5Gc joint laying system is simple but effective: fitters can lay the boards without using glue. The system helps reduce laying times, and no special tools are necessary.

As a result, the parquet can be removed and laid in a new home, or a damaged board replaced if necessary.



### RELATED ACCESSORIES

|  |  |  |  |  | PAGE      |
|---|---|---|---|---|-----------|
| SKIRTING BOARD  | SKIRTING BOARD  | STAIR ROUND FRONT NOSE  | SQUARE STAIR NOSE   | SQUARE STAIR NOSE - DOUBLE JOINT  | <b>60</b> |